1 and 1

system 10. Top portion 34 and lower portion 36 are preferably secured to one another by a suitable attachment means as a zipper, a hook and loop fastener, etc. Top portion 34 of cover 32 presents the sleep surface 37 to the user.

Base pad 38 may comprise a thickness of foam that extends from interior 40 of center wall 16 to interior 42 of side wall 22. One or more of base pads 38 may be placed below one or both of fluid chambers 12 and 14. Base pad 38 is used to lift fluid chamber 12 and/or 14 to a level that is substantially even with the top 44 of side walls 22. Because base pad 38 is performing a lifting function, the foam comprising base pad 38 is preferably of a stiffer nature, e.g., L9 foam, than the foam of topper pad 19. Base pad 38 is of an appropriate thickness, e.g., 1 inch, to lift fluid chamber 12 and/or 14 to a position that is substantially level with the top 44 of side walls 22 when fluid chamber 12 and/or 14 is at a user's adjusted and desired pressure level.

## IN THE CLAIMS:

Please add the following new claims 26-36:

26. A system for sleep surface adjustment, wherein said sleep surface is provided by a sleep support system that is configured for a least two users, wherein said sleep surface is supported by a least two fluid chambers whose pressure is independently adjustable, and wherein said two fluid chambers are surrounded by an upper wall, a lower wall and a pair of side walls each having an interior and exterior, said system comprising:

a topper pad, said topper pad positioned above said fluid chambers and extending from said exterior of one of said pair of side walls to said exterior of the other of said pair of side walls;

a cover encasing said topper pad, said upper wall, said lower wall and said pair of side walls; and

a base pad positioned below at least one of said fluid chambers and used to raise said fluid chamber to a desired height if necessary to reach said desired height, said base pad comprising an additional fluid chamber.

27. The system of claim 26, wherein said additional fluid chamber has an independently adjustable fluid pressure setting.

19

- 2 -

A